



Commercial Roofing Solutions™

Contractor Series	
Please Distribute to:	Sales, Estimators & Project Managers

FEATURED PRODUCT LINE: **Reinforced EPDM with Batten-In-The-Seam Mechanical Attachment**

PRODUCTS USED: Firestone Reinforced EPDM (45, 60, or 75 mil), Firestone Batten Strips or V-Plates, Firestone Fasteners, Firestone ISO 95+ or DensDeck

SYSTEM BRIEF: Substrate board is fastened to deck at appropriate rate for board & thickness, and deck type, reinforced EPDM is laid out with min. 6" overlap, fastening unit (fastener and batten or plate) is located between the plies of EPDM in the middle of the 6" seam; seam is constructed with 6" QuickSeam Tape.

APPLICABILITY: **Excellent Cold Weather Solution** for Reroof, Tear-off, or New Construction Steel, Wood, Concrete, Tectum, and Gypsum Decks

WARRANTY INFO: 5, 10, 15, 20* Year Red Shield Warranty Available
*20 year warranty applicable for recover, tear-off and new construction.

CODE RATINGS: FM Class I-90 when in-seam fastened 6" o.c. with Heavy Duty Fasteners*
UL Class A over ISO insulation on non-combustible deck; 1/2" slope max.**
*12" o.c. will achieve FM I-90 when HD Plus Fasteners are used with the Metal Batten Coil only.
** UL Class A on unlimited slope available - Contact Your Firestone Rep for more info.

SUMMARY: The mechanically fastened reinforced EPDM system is a light-weight, high performance roofing system that provides excellent wind uplift and external flame spread resistance properties. In addition, this system is an excellent choice for cold weather applications because of the minimal use of adhesives. It installs very quickly and it is a relatively simple system to install.

**For Pricing, Availability and More Information,
Call AAdvanced Building Products, LLC
1-800-498-3975**

THE ABOVE IS INTENDED FOR GENERAL INFORMATION ONLY. PLEASE REFER TO FIRESTONE TECHNICAL MANUALS FOR ALL SYSTEM REQUIREMENTS.