



Commercial Roofing Solutions™

Contractor Series	
Please Distribute to:	Sales, Estimators & Project Managers

FEATURED PRODUCT LINE: **2 Ply Mechanically Anchored SBS Modified Bitumen System**

PRODUCTS USED: Firestone SBS PolyTorch Base covered with Firestone SBS Torch Cap
Firestone Heavy Duty Fasteners with 2" Metal Lap Plates

SYSTEM BRIEF: Insulation is fastened @ 5 fasteners and insul plates per 4'x8' board,
Firestone PolyTorch Base is applied over insulation, fastened 12" or 18"
on center in 4" side laps only, the laps are torched watertight and an SBS
Torch Cap (standard, premium, or FR) is torched to the PolyTorch Base.

APPLICABILITY: Recover, Tear-off, or New Construction
Steel, Wood, or Concrete Decks

WARRANTY INFO: 5, 10, 15, 20 Year Red Shield Warranty Available

CODE RATINGS: Several Factory Mutual ratings are available.*
UL Class A over ISO insulation on non-combustible deck; 1/4" slope max.**
*Firestone Heavy Duty Fastener with new 2" Metal Lap Plate Only.
**Other UL approved combinations available; Contact Your Firestone Rep for more info.

SUMMARY: The Mechanically Anchored 2 Ply SBS System is a versatile, high performance roofing system designed to install quickly providing up to 20 years of warrantable coverage from Firestone. With the PolyTorch Base mechanically fastened in place and torched or heat-fused together, this system enables the contractor to 'dry in' the building quickly in both tear-off and new construction. Recover assemblies are also 20 year warrantable.

**For Pricing, Availability and More Information,
Call AAdvanced Building Products, LLC
1-800-498-3975**

THE ABOVE IS INTENDED FOR GENERAL INFORMATION ONLY. PLEASE REFER TO FIRESTONE TECHNICAL MANUALS FOR ALL SYSTEM REQUIREMENTS.