



Commercial Roofing Solutions™

Contractor Series	
Please Distribute to:	Sales, Estimators & Project Managers

FEATURED PRODUCT LINE: 2 Ply SBS Modified Bitumen System
with Self-Adhered Base Sheet & Torch Cap

PRODUCTS USED: Firestone MB Base SA covered with Firestone SBS or APP Torch Cap
Firestone ISO 95+ or GP / Firestone DensDeck Prime

SYSTEM BRIEF: Substrate board is fastened at appropriate rate for board type & thickness, MB Base SA is unrolled & positioned over substrate board, release film is pulled away to allow base sheet to self-adhere to board, SBS or APP Cap Sheet is torch in place over self-adhering MB Base SA

APPLICABILITY: Reroof, Tear-off, or New Construction
Steel, Wood, or Concrete Decks

WARRANTY INFO: 5, 10, 15, 20, & 25* Year Red Shield Warranty Available
*25 year warranty applicable to tear-off and new construction only; AcryliTop Coating System required

CODE RATINGS: Factory Mutual ratings up to class I-165 on steel deck.**
UL Class A over ISO insulation on non-combustible deck; 1/4" slope max.**

**Other UL approved combinations available; Contact Your Firestone Rep for more info.

SUMMARY: The Self-Adhered base with a torch granule cap system is a versatile, high performance roofing system designed to install quickly providing up to 20 years of warrantable coverage from Firestone. This system enables the contractor to 'dry in' the building quickly in recover and new construction. Re-roofing assemblies are 20 year warrantable and new construction or total tear-offs are 25 year warrantable assemblies with the AcryliTop PC 100 Coating System applied.

For Pricing, Availability and More Information,
Call AAdvanced Building Products, LLC
1-800-498-3975