

## FIRESTONE RED SHIELD WARRANTIES FOR ULTRAPLY TPO

| Warranty Length | System Type                                       | Insulation Type  | Insulation Attachment               | Membrane Gauge       | Membrane Attachment<br>(Single or Wide Weld) |
|-----------------|---|--|-------------------------------------|----------------------|--|
| 5-15            | Fully Adhered<br>8', 10', 12'<br>sheet            | Min. 1.0" ISO<br>CoverDeck<br>Dens Deck®<br>½" WoodFiber | Approved<br>Fastener or<br>Adhesive | .045"/.060"<br>.080" | Fully Adhered                                |
| 5-15            | Mechanically<br>Attached<br>8', 10', 12'<br>sheet | Min. 1.0" ISO<br>CoverDeck<br>Dens Deck®<br>½" WoodFiber | Approved<br>Fastener                | .045"/.060"<br>.080" | 12" oc                                       |
| 5-15            | Ballasted<br>8', 10', 12'<br>sheet                | Min. 1.0" ISO<br>CoverDeck<br>½" WoodFiber               | Loose Laid/<br>Approved<br>Adhesive | .045"/.060"<br>.080" | Loose Laid<br>with Ballast                   |
| 20*             | Fully Adhered<br>8', 10', 12'<br>sheet            | Min. 1.0" ISO<br>CoverDeck<br>Dens Deck®                 | Approved<br>Fastener or<br>Adhesive | .045"/.060"<br>.080" | Fully Adhered                                |
| 20*             | Mechanically<br>Attached<br>8', 10', 12'<br>sheet | Min. 1.0" ISO<br>CoverDeck<br>Dens Deck®                 | Approved<br>Fastener                | .045"                | 6" oc  |
| 20              | Mechanically<br>Attached<br>8', 10', 12'<br>sheet | Min. 1.0" ISO<br>CoverDeck<br>Dens Deck®                 | Approved<br>Fastener                | .060"/.080"          | 12" oc                                       |
| 20*             | Ballasted<br>8', 10', 12'<br>sheet                | Min. 1.0" ISO<br>CoverDeck                               | Loose Laid/<br>Approved<br>Adhesive | .045"/.060"<br>.080" | Loose Laid<br>with Ballast                   |
| 25*             | Fully Adhered<br>8', 10' sheet                    | Min. 1.0" ISO<br>CoverDeck<br>Dens Deck®                 | Approved<br>Fastener or<br>Adhesive | .060"/.080"          | Fully Adhered                                |
| 25*             | Mechanically<br>Attached<br>8', 10' sheet         | Min. 1.0" ISO<br>CoverDeck<br>Dens Deck®                 | Approved<br>Fastener                | .060"/.080"          | 6" oc  |
| 30              | Fully Adhered<br>8', 10' sheet                    | Min. 1.0" ISO<br>CoverDeck<br>Dens Deck®                 | Approved<br>Fastener or<br>Adhesive | .080"                | Fully Adhered                                |
| 30              | Mechanically<br>Attached<br>8' sheet              | Min. 1.0" ISO<br>CoverDeck<br>Dens Deck®                 | Approved<br>Fastener                | .080"                | 6" oc  |

\*(New Warranty Options)

**Note:** For specific system requirements, please refer to the Firestone Technical Database at [www.firestonebpc.com](http://www.firestonebpc.com). This chart is intended for reference only and should only be used in conjunction with the Technical Database. For further assistance, please contact your local Firestone Sales Representative or Firestone Technical Services at 1-800-428-4511.